

SECTION 1. Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product code : Hygienfresh DeoMatic Spray Note di Pulito

Trades code : A75-015

Product line: HygienFresh

UFI: 5471-P0AV-R00C-C0AJ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Deodorant for Automatic Dispenser with super perfuming concentrated essence

Sectors of use:

Private households (= general public = consumers)[SU21], Public domain (administration, education, entertainment, services, craftsmen)[SU22]

Uses advised against

Do not use for purposes other than those listed

1.3. Details of the supplier of the safety data sheet

Tintolav s.r.l. - Via M. D' Antona 7 - 10028 Trofarello (TO) Tel. 011/649.68.27 Fax 011/649.67.42

Email: info@tintolav.com - Sito internet: www.tintolav.com

Email tecnico competente: a.conedera@tintolav.com

National contact: Malta: Emergency Ambulance 112

Accident & Emergency Department 2545 4030

1.4. Emergency telephone number

The UK National Poisons Emergency number +44 (0)870 600 6266

London: Emergency 24 hour telephone +44 (0) 207188 0100

SECTION 2. Hazards identification**2.1. Classification of the substance or mixture**

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms:

GHS02, GHS07

Hazard Class and Category Code(s):

Flam. Aerosol 1, Skin Sens. 1B, Eye Irrit. 2, Aquatic Chronic 3

Hazard statement Code(s):

H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H412 - Harmful to aquatic life with long lasting effects.

Aerosol that ignites easily even at low temperatures, fire risk

If brought into contact with eyes, the product, causes significant irritations which may last for more than 24 hours.

The product, if brought into contact with skin can cause skin sensitization.

The product is dangerous to the environment as it is harmful to aquatic life with long lasting effects

Issued on 03/02/2022 - Rel. # 2 on 03/02/2022

2 / 18

In conformity to Regulation (EU) 2020/878

The repeated inhalation of vapors can cause drowsiness and giddiness.
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 ° C.
The aerosol containers overheated burst and can be ejected with violence from a distance and can take place a dangerous mechanism for the fire.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008:

Pictogram, Signal Word Code(s):
GHS02, GHS07 - Danger



Hazard statement Code(s):
H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H412 - Harmful to aquatic life with long lasting effects.

Supplemental Hazard statement Code(s):
not applicable

Precautionary statements:

General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

Response

P302+P352 - IF ON SKIN: Wash with plenty of water and soap.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

Storage

P403 - Store in a well-ventilated place.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Disposal

P501 - Dispose of contents / container in accordance with local and national regulations.

Contains:

butane, isobutane, propane, alcohol, parfum, benzyl salicylate, hexyl cinnamal, hexyl salicylate, tetramethyl acetyloctahydronaphthalenes, geraniol, citronellol, eugenol, coumarin, hydroxycitronellal.

Content of VOC ready to use condition: 94,16 %

UFI: 5471-P0AV-R00C-C0AJ

2.3. Other hazards

The substance / mixture NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

No information on other hazards

SECTION 3. Composition/information on ingredients
3.1 Substances

Irrelevant

3.2 Mixtures

Refer to paragraph 16 for full text of hazard statements

Butane contains less than 0,1 % w/w 1,3-butadiene (EINECS No 203-450-8)

Note K - The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w 1,3- butadiene (Einecs No 203-450-8), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 shall apply.

Allergens contained:

7-idrossictronellale = 0,144

Alpha isomethyl ionone = 0,054

Benzyl alcohol = 0,001

Benzyl benzoate = 0,002

Cinnamyl alcohol = 0,000

Citral = 0,000

Citronellol = 0,175

Coumarin = 0,144

D-Limonene ((S)-p-menta-1,8-diene) = 0,018

Eugenol = 0,144

Farnesol = 0,000

Geraniol = 0,180

Isoeugenol = 0,000

Salicilato di benzile = 0,781

dipentene = 0,018

linalolo = 0,067

α-Hexylcinnamaldehyde = 0,480

Substance	Concentration[w/w]	Classification	Index	CAS	EINECS	REACH
Butane Note: K	>= 35 < 50%	Flam. Gas 1A, H220 ATE inhal = 658,0mg/l/4 h	601-004-00-0	106-97-8	203-448-7	01-2119474 691-32
Isobutane	>= 15 < 25%	Flam. Gas 1A, H220 ATE oral = 570.000,0 mg/kg ATE dermal = 570.000,0 mg/kg ATE inhal = 658.000,0mg/l/4 h	601-004-00-0	75-28-5	200-857-2	01-2119485 395-27
ethanol	>= 15 < 25%	Flam. Liq. 2, H225 ATE oral = 7.060,0 mg/kg ATE dermal = 20.000,0 mg/kg ATE inhal = 20.000,0mg/l/4 h	603-002-00-5	64-17-5	200-578-6	01-2119457 610-43
Propane	>= 15 < 25%	Flam. Gas 1A, H220; Press. Gas, H280	601-003-00-5	74-98-6	200-827-9	01-2119486 944-21

Substance	Concentration[w/w]	Classification	Index	CAS	EINECS	REACH
		ATE inhal = 410.000,0mg/l/4 h				
Benzyl salicylate	>= 0,1 < 1%	Skin Sens. 1B, H317; Eye Irrit. 2, H319; Aquatic Chronic 3, H412 1 1 ATE oral = 2.227,0 mg/kg	607-754-00-5	118-58-1	204-262-9	01-2119969 442-31
α-Hexylcinnamaldehyde	>= 0,1 < 1%	Skin Sens. 1, H317; Aquatic Chronic 2, H411 ATE oral = 2.450,0 mg/kg	ND	101-86-0	202-983-3	01-2119533 092-50
Hexyl salicylate - FEMA 0	>= 0,1 < 1%	Skin Irrit. 2, H315; Skin Sens. 1, H317; Eye Irrit. 2, H319; Aquatic Acute 1, H400; Aquatic Chronic 1, H410 1 1 ATE oral = 5.000,0 mg/kg ATE dermal = 5.000,0 mg/kg	ND	6259-76-3	228-408-6	01-2119638 275-36-000 2
Geraniol - FEMA 2507	>= 0,1 < 1%	Skin Irrit. 2, H315; Skin Sens. 1, H317; Eye Dam. 1, H318 ATE oral = 3.500,0 mg/kg ATE dermal = 5.000,0 mg/kg ATE inhal = 0,5mg/l/4 h	603-241-00-5	106-24-1	203-377-1	01-2119552 430-49-000 0
Citronellol	>= 0,1 < 1%	Skin Irrit. 2, H315; Skin Sens. 1B, H317; Eye Irrit. 2, H319; STOT SE 3, H335 ATE oral = 3.450,0 mg/kg ATE dermal = 2.650,0 mg/kg ATE inhal = 1,3mg/l/4 h	ND	106-22-9	203-375-0	01-2119453 995-23-000 0
1-(2,3,8,8-Tetramethyl-1,2,3,4,5,6,7,8-octahydronaphthalen-2-yl)ethanone - FEMA 0	>= 0,1 < 1%	Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 1, H410 1 1 ATE oral = 5.000,0 mg/kg ATE dermal = 5.000,0 mg/kg	ND	54464-57-2	259-174-3	01-2119489 989-04
Eugenol	>= 0,1 < 1%	Skin Sens. 1B, H317; Eye Irrit. 2, H319 ATE oral = 2.000,0 mg/kg	ND	97-53-0	202-589-1	01-2119971 802-33-000 0
Coumarin	>= 0,1 < 1%	Acute Tox. 4, H302; Skin Sens. 1, H317;	ND	91-64-5	202-086-7	01-2119943 756-26-00

Substance	Concentration[w/w]	Classification	Index	CAS	EINECS	REACH
		STOT RE 2, H373 ATE oral = 293,0 mg/kg ATE dermal = 242,0 mg/kg				00
7-hydroxycitronellal	>= 0,1 < 1%	Skin Irrit. 2, H315; Skin Sens. 1, H317; Eye Dam. 1, H318; Eye Irrit. 2, H319 ATE oral = 5.000,0 mg/kg	ND	107-75-5	ND	NR
Benzophenone - FEMA 2134	>= 0,1 < 1%	Aquatic Acute 1, H400; Aquatic Chronic 2, H411 1 1 ATE oral = 10.000,0 mg/kg ATE dermal = 3.535,0 mg/kg	ND	119-61-9	204-337-6	NR

Fractionated global values

H317 = 1,81	H319 = 1,73	H412 = 0,81	H302 = 0,44
H411 = 1,01	H400 = 0,43	H315 = 1,39	H410 = 0,51
H318 = 0,16	H335 = 0,11	H373 = 0,07	H226 = 0,02
H304 = 0,01	H361 = 0,02	H311 = 0,00	H301 = 0,00
H314 = 0,00	H225 = 18,02	H220 = 75,86	H280 = 16,69
H332 = 0,02			

SECTION 4. First aid measures
4.1. Description of first aid measures
Inhalation:

Air the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated area. If you feel unwell seek medical advice.

Direct contact with skin (of the pure product):

Take contaminated clothing Immediately off.

Wash immediately with plenty of running water and possibly with soap, the areas of the body that have, or are only suspected to have, come in contact with the product.

In case of contact with skin, wash immediately with water and soap.

Direct contact with eyes (of the pure product):

Wash immediately and thoroughly with running water, keeping eyelids open for at least 10 minutes, then protect your eyes with a dry sterile gauze. Seek medical advice immediately

Ingestion:

Not hazardous. It's possible to give activated charcoal in water or liquid paraffin medicine

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If medical advice is needed, have product container or label at hand.

SECTION 5. Firefighting measures**5.1. Extinguishing media**

Advised extinguishing agents:

CO2 or dry powder extinguisher

Extinguishing means to avoid:

Direct jets of water

5.2. Special hazards arising from the substance or mixture

The aerosol containers overheated burst and can be ejected with violence from a distance and can take place a dangerous mechanism for the fire.

Manufactured under pressure in sealed metal container (test pressure 15 bar max). Cool containers with water spray trying to remove them from the fire. The aerosol containers can be overheated and burst violently ejected from a distance (protect the head using a safety helmet).

5.3. Advice for firefighters

Use protection for the breathing apparatus

Safety helmet and full protective suit.

The spray water can be used to protect the people involved in the extinction

You may also use selfrespirator, especially when working in confined and poorly ventilated area and if you use halogenated extinguishers (Halon 1211 fluobrene, Solkan 123, NAF, etc...)

Keep containers cool with water spray

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****6.1.1 For non-emergency personnel:**

Leave the area surrounding the spill or release. Do not smoke

Leave the surrounding area recalling that any overheating could project the cylinder at a considerable distance.

Wear gloves and protective clothing

6.1.2 For emergency responders:

Given the tightness of aerosol, it is unlikely that the spillage may occur.

However if some container is damaged likely to cause a loss, insulate the tank in question by bringing it to open air or covering it with inert material and fuel (eg sand, earth, vermiculite) and having the care to avoid any point of ignition that might pose a serious risk of fire.

Wear gloves and protective clothing Suitable: LaTeX, nitrile, PVC

Eliminate all unguarded flames and possible sources of ignition. No smoking.

Provision of sufficient ventilation.

Evacuate the danger area and, in case, consult an expert.

6.2. Environmental precautions

Contain spill

Inform the competent authorities.

Discharge the remains in compliance with the regulations

6.3. Methods and material for containment and cleaning up

6.3.1 For containment:

Rapidly recover the product, wear a mask and protective clothing
Recover the product for reuse, if possible, or the removal.

6.3.2 For cleaning up:

After wiping up, wash with water the area and materials involved

6.3.3 Other information:

None in particular.

6.4. Reference to other sections

Refer to paragraphs 8 and 13 for more information

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid contact and inhalation of vapors

Use extreme caution when handling the product. Avoid shock or friction.

Do not smoke at work

At work do not eat or drink.

Vapors are heavier than air and may spread close to the ground and form explosive mixtures with air. Prevent formation of flammable or explosive concentrations in the air.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 ° C.

Do not pierce or burn, even after the use. Do not spray on flame or incandescent objects. Use in adequately ventilated areas.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

See also paragraph 8 below.

7.2. Conditions for safe storage, including any incompatibilities

Keep in original container closed tightly. Do not store in open or unlabeled containers.

Keep containers upright and safe by avoiding the possibility of falls or collisions.

Pressurized container. Store in a ventilated place, in original packaging away from heat and sunlight.

Always store in well ventilated areas.

Never close the container tightly, leave a chance to vent

Keep away from open flames, sparks and heat sources. Avoid direct sunlight exposure.

7.3. Specific end use(s)

Private households (= general public = consumers):

Handle with care.

Store in ventilated place away from heat sources,

Keep the container tightly closed.

Public domain (administration, education, entertainment, services, craftsmen):

Handle with care. Store in a ventilated area and away from heat, keep the container tightly closed.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Related to contained substances:

Issued on 03/02/2022 - Rel. # 2 on 03/02/2022

8 / 18

In conformity to Regulation (EU) 2020/878

Butane:

TLV (ACGIH) = 1000 ppm

ACGIH TLV (United States, 3/2012).

TWA: 1000 ppm 8 hour (s).

NIOSH REL (United States, 1/2013).

TWA: 1900 mg/m 10 hour (s).

TWA: 800 ppm 10 hour (s).

OSHA PEL 1989 (United States, 3/1989).

TWA: 1900 mg/m 8 hour (s).

TWA: 800 ppm 8 hour (s).

Butane EH40 WEL TWA 600 ppm 1.450 mg/m³**Isobutane:**

ACGIH TLV (United States, 3/2012).

TWA: 1000 ppm 8 hour (s).

NIOSH REL (United States, 1/2013).

TWA: 1900 mg/m 10 hour (s).

TWA: 800 ppm 10 hour (s)

ethanol:

Component CAS-No. Value Control parameters

Basis

Ethanol-17-64 TWA 5 ppm 1.000

1.920 mg/m³

UK. EH40 WEL-Workplace Exposure Limits

Remarks Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used

Propane:

TLV: (Aliphatic hydrocarbon gases) 1000 ppm as TWA; (ACGIH 2005).

ACGIH TLV (United States, 3/2012).

TWA: 1000 ppm 8 hour (s).

NIOSH REL (United States, 1/2013).

TWA: 1800 mg/m 10 hour (s).

TWA: 1000 ppm 10 hour (s).

OSHA PEL (United States, 6/2010).

TWA: 1800 mg/m 8 hour (s).

TWA: 1000 ppm 8 hour (s).

OSHA PEL 1989 (United States, 3/1989).

TWA: 1800 mg/m 8 hour (s).

TWA: 1000 ppm 8 hour (s)

- Substance: ethanol

DNELSystemic effects Long term Workers inhalation = 950 (mg/m³)

Systemic effects Long term Workers dermal = 343 (mg/kg bw/day)

Systemic effects Long term Consumers inhalation = 114 (mg/m³)

Systemic effects Long term Consumers dermal = 206 (mg/kg bw/day)

Systemic effects Long term Consumers oral = 87 (mg/kg bw/day)

PNEC

Sweet water = 0,96 (mg/l)

sediment Sweet water = 3,6 (mg/kg/sediment)

Sea water = 0,79 (mg/l)

sediment Sea water = 2,9 (mg/kg/sediment)

intermittent emissions = 2,75 (mg/l)

STP = 580 (mg/l)

ground = 0,63 (mg/kg ground)

Issued on 03/02/2022 - Rel. # 2 on 03/02/2022

9 / 18

In conformity to Regulation (EU) 2020/878

- Substance: α -Hexylcinnamaldehyde

DNEL

Systemic effects Long term Workers inhalation = 0,000078 (mg/m³)Systemic effects Short term Workers inhalation = 0,00628 (mg/m³)

PNEC

Sweet water = 0,03 (mg/l)

sediment Sweet water = 47,7 (mg/kg/sediment)

Sea water = 0,003 (mg/l)

sediment Sea water = 4,77 (mg/kg/sediment)

ground = 9,51 (mg/kg ground)

- Substance: Hexyl salicylate

DNEL

Systemic effects Long term Workers inhalation = 0,79 (mg/m³)

Systemic effects Long term Workers dermal = 2083 (mg/kg bw/day)

Systemic effects Short term Workers inhalation = 0,79 (mg/m³)

Systemic effects Short term Workers dermal = 2083 (mg/kg bw/day)

- Substance: Geraniol

DNEL

Systemic effects Long term Workers inhalation = 161,6 (mg/m³)

- Substance: Citronellol

DNEL

Systemic effects Long term Workers inhalation = 161,6 (mg/m³)

- Substance: 1-(2,3,8,8-Tetramethyl-1,2,3,4,5,6,7,8-octahydronaphthalen-2-yl)ethanone

DNEL

Systemic effects Long term Workers inhalation = 1,76 (mg/m³)

Systemic effects Long term Workers dermal = 1,73 (mg/kg bw/day)

Systemic effects Short term Workers inhalation = 1,76 (mg/m³)

Systemic effects Short term Workers dermal = 1,73 (mg/kg bw/day)

PNEC

Sweet water = 0,0028 (mg/l)

sediment Sweet water = 3,73 (mg/kg/sediment)

Sea water = 0,00028 (mg/l)

sediment Sea water = 0,75 (mg/kg/sediment)

ground = 0,705 (mg/kg ground)

8.2. Exposure controls

Appropriate engineering controls:

Private households (= general public = consumers):

No specific checks planned

Public domain (administration, education, entertainment, services, craftsmen):

No specific monitoring foreseen

Individual protection measures:

(a) Eye / face protection

Wear safety goggles to EN-166



(b) Skin protection

(i) Hand protection

Manipulate with gloves. The gloves should be checked before being used. Use a technique suitable for the removal of gloves (without touching the outside of the glove) to avoid skin contact with this product dispose of contaminated gloves after use in accordance with the legislation and good laboratory practices. Wash and dry your hands.
Selected protective gloves shall comply with the requirements of EU Directive 89/686/EEC and EN 374 standards arising therefrom.

Full contact

Material: nitrile rubber

minimum thickness: 0.11 mm

permeation time: 480 min

(ii) Other

Avoid direct contact with the skin

Better is to use cotton antistatic clothing

(c) Respiratory protection

Work in a sufficiently ventilated to avoid inhaling the product.

(d) Thermal hazards

No hazard to report

Environmental exposure controls:

Use according to good working practices to avoid pollution into the environment.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical and chemical properties	Value	Determination method
Appearance	Aerosol	
Colour	colorless liquid under pressure	
Odour	characteristic	
Odour threshold	not determined	
pH	irrelevant	
Melting point/freezing point	< -100 °C (liquid gas)	
Initial boiling point and boiling range	> -42 °C (liquid gas)	
Flash point	< -80 °C (liquid gas)	ASTM D92
Evaporation rate	irrelevant	
Flammability (solid, gas)	flammable	
Upper/lower flammability or explosive limits	9,5% vol / 1,8% vol	
Vapour pressure	3,2 bar	
Vapour density	> 2 (liquid gas)	
Relative density	0,65 kg/l	
Solubility	irrelevant	
Water solubility	not determined	
Partition coefficient: n-octanol/water	not determined	
Auto-ignition temperature	> 400 °C	
Decomposition temperature	not determined	

Physical and chemical properties	Value	Determination method
Viscosity	not determined	
Explosive properties	may burst if heated.	
Oxidising properties	non-oxidizing	
Container volume	335 ml	
Product volume	250 ml	
Pressure to 20°C	3.2 bar	
Deformation pressure	16.5 bar	
Burst pressure of the container	18 bar	
Flash point of liquid phase	< 21 °C	
Propellant inflammability	< 0 °C	

9.2. Other information

Content of VOC ready to use condition: 94,16 %

SECTION 10. Stability and reactivity

10.1. Reactivity

No reactivity hazards

10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.

10.3. Possibility of hazardous reactions

There are no hazardous reactions

10.4. Conditions to avoid

Avoid heating the product, it could explode.

Avoid contact with combustible materials. The product could catch fire.

heat, open flames, sparks or hot surfaces.

The aerosol product is stable for a period exceeding 36 months and in normal storage conditions can not take place dangerous reactions as the container is almost hermetically sealed.

To avoid that the metal container can deteriorate, keep away from acidic or basic products. Attention to the heat as temperatures exceeding 50 ° C has increased pressure inside the container that gets to deformation of the cylinder until the outbreak.

10.5. Incompatible materials

It can generate inflammable gases to contact with elementary metals, nitrides, strong reducing agents.

It can generate toxic gases to contact with oxidants mineral acids, organic peroxides, organic water peroxides.

It can ignite in contact with oxidants mineral acids, organic nitrides, peroxides and water peroxides, strong oxidants agents.

10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11. Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

ATE(mix) oral = 144.386,6 mg/kg

ATE(mix) dermal = ∞ ATE(mix) inhal = ∞

(a) acute toxicity: ethanol: LD50 Oral-rat-7.060 mg/kg

Remarks: Lungs, Thorax, or Respiration: Other changes.

LC50 Inhalation-rat-10:0-20000 ppm

Benzyl salicylate: Oral Rat LD50 = 2227 mg/kg bw

 α -Hexylcinnamaldehyde: Oral (rat) LD50: 2450 mg/kg

Geraniol: LD50 Oral (rat) (mg / kg body weight) = 3500

LD50 Dermal (rabbit) (mg / kg body weight) => 5000

LC50 Inhalation (rat) of vapor / dust / aerosol / smoke (mg / l / 4h): 0.5

Citronellol: orl-rat LD50:3450 mg/kg

skn-rbt LD50:2650 mg/kg

ihl-rat LCLo:1.3 mg/m³/4H

1-(2,3,8,8-Tetramethyl-1,2,3,4,5,6,7,8-octahydronaphthalen-2-yl)ethanone: TOXIC DOSE 1-LD > 50 5000 mg/kg (oral rat)

TOXIC DOSE 2-LD > 50 5000 mg/kg (skn-rbt)

Benzophenone: LD50 Oral - rat - > 10,000 mg/kg

LD50 Dermal - rabbit - 3,535 mg/kg

(b) skin corrosion/irritation: ethanol: Skin-rabbit

Result: Irritating to skin. -12:0 am

Benzyl salicylate: Skin - rabbit

Result: No skin irritation

(OECD Test Guideline 404)

Geraniol: skn-rbt 100 mg/24H SEV

skn-gpg 100 mg/24H SEV

skn-man 16 mg/24H SEV

Citronellol: skn-rbt 100 mg/24H SEV

Skin - Human - Skin irritation - 48 h

(c) serious eye damage/irritation: If brought into contact with eyes, the product, causes significant irritations which may last for more than 24 hours.

ethanol: Eyes-rabbit

Result: Mild eye irritation-12:0 am

(Draize Test)

Geraniol: Eyes-rabbit

Result: Risk of serious damage to eyes. -12:00 am

(Directive 67/548/EEC, Annex V, b. 5.)

Benzyl salicylate: Eyes - In vitro study

Result: Moderate eye irritation

(OECD Test Guideline 437)

Eyes - rabbit

Result: Irritating to eyes.

(Draize Test)

(d) respiratory or skin sensitisation: The product, if brought into contact with skin can cause skin sensitization.

Geraniol: Guinea pig

May cause sensitisation by skin contact.

Citronellol: mouse - May cause sensitization by skin contact.

Coumarin: Test: Inhalation Sensitization Route: Inhalation Species: Rat = 293 mg/kg

Test: Inhalation Sensitization Route: Inhalation Species: Mouse = 196 mg/kg

(e) germ cell mutagenicity: based on available data, the classification criteria are not met.

(f) carcinogenicity: Geraniol: No component of this product present at levels greater than or equal to 0.1% is identified

as

probable, possible or confirmed human carcinogen by IARC.

(g) eproductivetoxicity: ethanol: Reproductive toxicity-Human-female-Oral

Effects on Newborn: Apgar score (human only). Effects on Newborn: Other measures or neonatal effects.

Effects on Newborn: Drug dependence.

(h) specific target organ toxicity (STOT) single exposure: based on available data, the classification criteria are not met.

(i) specific target organ toxicity (STOT) repeated exposure based on available data, the classification criteria are not met.

(j) aspiration hazard: Benzyl salicylate: in vivo assay - mouse

May cause allergic skin reaction.

(OECD Test Guideline 429)

Related to contained substances:

Butane:

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 658

Isobutane:

LD50 (rat) Oral (mg/kg body weight) = 570000

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 570000

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 658000

ethanol:

ROUTES of EXPOSURE: the substance can be absorbed into the body by inhalation of its fumes and ingestion.

INHALATION RISK: A harmful contamination of the air will be reached quite slowly due to evaporation of the substance at 20 C.

Effects of short-term exposure: the substance is irritating to the eyes. Inhalation of high vapour can concetrazioni cause irritation of the eyes and respiratory tract. The substance may cause effects on the central nervous system effects of REPEATED EXPOSURE or long term: the liquid degreasing the skin features. The substance may have an effect on the high central nervous system respiratory tract, causing irritation, headaches, fatigue and lack of concentration. See Notes.

ACUTE HAZARDS/Symptoms INHALATION Cough. Headaches. Fatigue. Drowsiness.

CUTE CUTE.

EYE Redness. Pain. Burning.

SWALLOWED burning sensation. Headaches. Confusion. Vertigo. State of unconsciousness.

N O T and consumption of ethanol during pregnancy can have adverse effects on the unborn child. Chronic ethanol ingestion can cause cirrhosis of the liver.

LD50 (rat) Oral (mg/kg body weight) = 7060

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 20000

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 20000

Propane:

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 410000

Benzyl salicylate:

LD50 (rat) Oral (mg/kg body weight) = 2227

α -Hexylcinnamaldehyde:

LD50 (rat) Oral (mg/kg body weight) = 2450

Hexyl salicylate:

LD50 (rat) Oral (mg/kg body weight) = 5000

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 5000

Geraniol:

LD50 (rat) Oral (mg/kg body weight) = 3500

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 5000

Issued on 03/02/2022 - Rel. # 2 on 03/02/2022

14 / 18

In conformity to Regulation (EU) 2020/878

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 0,5

Citronellol:

LD50 (rat) Oral (mg/kg body weight) = 3450

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 2650

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 1,3

1-(2,3,8,8-Tetramethyl-1,2,3,4,5,6,7,8-octahydronaphthalen-2-yl)ethanone:

LD50 (rat) Oral (mg/kg body weight) = 5000

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 5000

Eugenol:

LD50 (rat) Oral (mg/kg body weight) = 2000

Coumarin:

Acute oral LD50 for rats: 293mg/kg

Acute oral LD50 for mice: 196mg/kg

Irritant data: Not determined

Inhalation data: Not determined

Mutagenicity data: Not determined

LD50 (rat) Oral (mg/kg body weight) = 293

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 242

7-hydroxycitronellal:

LD50 (rat) Oral (mg/kg body weight) = 5000

Benzophenone:

LD50 (rat) Oral (mg/kg body weight) = 10000

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 3535

11.2. Information on other hazards

No data available.

SECTION 12. Ecological information**12.1. Toxicity**

Related to contained substances:

Butane:

C(E)L50 (mg/l) = 7,71

Isobutane:

C(E)L50 (mg/l) = 7,71

ethanol:

C(E)L50 (mg/l) = 11200

Propane:

C(E)L50 (mg/l) = 7,71

Benzyl salicylate:

Zebra fish (Brachydanio rerio) 96 hour LC50 = 1.03 mg/L

48 hour LC50 = 1.4mg/l

C(E)L50 (mg/l) = 1,03

 α -Hexylcinnamaldehyde:

Issued on 03/02/2022 - Rel. # 2 on 03/02/2022

15 / 18

In conformity to Regulation (EU) 2020/878

Freshwater Fish Toxicity: acute LC50 >1-10 mg/L
Freshwater Invertebrates Toxicity: acute EC <1 mg/L
Algal Toxicity: acute EC <1 mg/L.
C(E)L50 (mg/l) = 0,99

Geraniol:
static test LC50-zebrafish (zebra fish)-ca. 22 mg/l-96 h (OECD Test Guideline 203)
Broadcast application EC50-Daphnia magna (Water flea)-10.8 mg/l-48 h (OECD Test Guideline 202)
Growth inhibition EC50-Desmodesmus subspicatus (green algae)-13.1 mg/l-72 h
C(E)L50 (mg/l) = 10,8

Citronellol:
LC50 (96 h) 14,66 mg/l, Leuciscus idus
EC50 (48 h) 17 mg/l, Daphnia magna
EC50 (72 h) 2,4 mg/l, Scenedesmus subspicatus
C(E)L50 (mg/l) = 2,4

1-(2,3,8,8-Tetramethyl-1,2,3,4,5,6,7,8-octahydronaphthalen-2-yl)ethanone:
Endpoint: LC50 species: lepomis macrochirus (fish-salt Bluegrill) = 1.30 mg/l-h Duration: 96-Note:: method: OECD 203 TG
Endpoint: EC50-species: Daphnia magna (Water flea) = 1.38 mg/l-h Duration: 48-comments:: semi-static test method: OECD TG 202
Endpoint: EC50 Desmodesmus subspicatus-species (green algae) = 2.60 mg/l-h Duration: 72-
Note:: static test method: OECD TG201
C(E)L50 (mg/l) = 1,3

Eugenol:
Toxicity to fish Lc50-Danio rerio (zebrafish)-13 mg/l-96 h (OECD TEST GUIDELINE 203) Toxicity to daphnia and other aquatic invertebrates – Daphnia Ec50-1.13 mg/l-48 h
C(E)L50 (mg/l) = 1,13

Coumarin:
Toxicity to fish LC50 - Poecilia reticulata (guppy) - 56 mg/l - 96 h
Toxicity to daphnia and other aquatic invertebrates LC50 - Daphnia magna (Water flea) - 3.5 mg/l - 48 h
C(E)L50 (mg/l) = 13,5

Benzophenone:
Toxicity to fish mortality NOEC - Pimephales promelas (fathead minnow) - 5.86 mg/l - 7.0 d
mortality LOEC - Pimephales promelas (fathead minnow) - 9.24 mg/l - 7.0 d
LC50 - Pimephales promelas (fathead minnow) - 14.2 mg/l - 96.0 h
Toxicity to daphnia and other aquatic invertebrates
EC50 - Daphnia magna (Water flea) - 0.28 mg/l - 24 h
C(E)L50 (mg/l) = 14,2

The product is dangerous for the environment as it is toxic for aquatic organisms following acute exposure.

Use according to good working practices to avoid pollution into the environment.

12.2. Persistence and degradability

Related to contained substances:

Geraniol:
Aerobic chemical oxygen demand:
Exposure time 3 days
Result: 80 - 100% - Easily biodegradable.
(OECD Test Guideline 301A)

12.3. Bioaccumulative potential

Related to contained substances:
Coumarin:
Bioaccumulation *Leuciscus idus melanotus* - 3 d -46 µg/l
Bioconcentration factor (BCF): < 10

12.4. Mobility in soil

Related to contained substances:
Geraniol:
log Pow: 3.47

12.5. Results of PBT and vPvB assessment

No PBT/vPvB ingredient is present

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No adverse effects

SECTION 13. Disposal considerations

13.1. Waste treatment methods

The waste must be disposed of in compliance with the regulations in force delivering empty containers for final disposal and equipped to safely handle pressurized containers containing flammable liquids and gas waste. The empty container heated to temperatures exceeding 70 ° C can burst.

Recover if possible. Send to authorized discharge plants or for incineration under controlled conditions. Operate according to local and National rules in force

SECTION 14. Transport information

14.1. UN number or ID number

ADR/RID/IMDG/ICAO-IATA: 1950

ADR exemption because compliance with the following characteristics:

Combination packagings: per inner packaging 1 L per package 30 Kg

Inner packagings placed in shrink-wrapped or stretch-wrapped trays: per inner packaging 1 L per package 20 Kg

14.2. UN proper shipping name

ADR/RID/IMDG: AEROSOL infiammabili



Issued on 03/02/2022 - Rel. # 2 on 03/02/2022

17 / 18

In conformity to Regulation (EU) 2020/878

ADR/RID/IMDG: AEROSOL flammable

ICAO-IATA: AEROSOL flammable

14.3. Transport hazard class(es)

ADR/RID/IMDG/ICAO-IATA: Class : 2

ADR/RID/IMDG/ICAO-IATA: Label : Limited quantities

ADR: Tunnel restriction code : D

ADR/RID/IMDG/ICAO-IATA: Limited quantities : 1 L

IMDG - EmS : F-D, S-U

14.4. Packing group

ADR/RID/IMDG/ICAO-IATA: --

14.5. Environmental hazards

ADR/RID/ICAO-IATA: Product is not environmentally hazardous

IMDG: Marine polluting agent : Not

14.6. Special precautions for user

No data available.

14.7. Maritime transport in bulk according to IMO instruments

It is not intended to carry bulk

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso category:

P3a - FLAMMABLE AEROSOLS

REGULATION (EU) No 1357/2014 - waste:

HP3 - Flammable

15.2. Chemical safety assessment

The supplier has made an assessment of chemical safety

SECTION 16. Other information**16.1. Other information**

Points modified compared to previous release: 1.1. Product identifier, 2.1. Classification of the substance or mixture, 2.2. Label elements, 2.3. Other hazards, 3.2 Mixtures, 4.1. Description of first aid measures, 7.2. Conditions for safe storage, including any incompatibilities, 8.1. Control parameters, 9.2. Other information, 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008, 12.1. Toxicity, 12.2. Persistence and degradability, 12.3. Bioaccumulative potential, 12.4. Mobility in soil, 12.5. Results of PBT and vPvB assessment, 12.6. Endocrine disrupting properties

Description of the hazard statements exposed to point 3

H220 = Extremely flammable gas.

H225 = Highly flammable liquid and vapour.

H280 = Contains gas under pressure; may explode if heated.

Issued on 03/02/2022 - Rel. # 2 on 03/02/2022

18 / 18

In conformity to Regulation (EU) 2020/878

H317 = May cause an allergic skin reaction.
H319 = Causes serious eye irritation.
H412 = Harmful to aquatic life with long lasting effects.
H411 = Toxic to aquatic life with long lasting effects.
H315 = Causes skin irritation.
H400 = Very toxic to aquatic life.
H410 = Very toxic to aquatic life with long lasting effects.
H318 = Causes serious eye damage.
H335 = May cause respiratory irritation.
H302 = Harmful if swallowed.
H373 = May cause damage to organs through prolonged or repeated exposure .

Classification based on data of all mixture components

Main normative references:

Directive 1999/45/EC

Directive 2001/60/EC

Regulation 1272/2008/EC

Regulation 2010/453/EC

** The information contained herein is based on our knowledge at the date above.

Related solely to the product and do not constitute a guarantee of a particular quality.

It is the duty of the user to ensure that these are appropriate and complete information regarding the specific use intended.

This data sheet cancels and replaces any previous edition.