

## **SECTION 1. Identification of the substance/mixture and of the company/undertaking**

### **1.1. Product identifier**

Product code : Hypnosense Ammorbidente Purity  
Trades code : AH45-015  
Product line: Hypnosense

UFI: KXM0-D00Q-T00E-4MSV

### **1.2. Relevant identified uses of the substance or mixture and uses advised against**

Concentrated softener with hyper resistant scent - resistant to drying

Sectors of use:

Industrial Manufacturing[SU3], Private households (= general public = consumers)[SU21], Public domain (administration, education, entertainment, services, craftsmen)[SU22]

Uses advised against

Do not use for purposes other than those listed

### **1.3. Details of the supplier of the safety data sheet**

Tintolav s.r.l. - Via M. D' Antona 7 - 10028 Trofarello (TO) Tel. 011/649.68.27 Fax 011/649.67.42

Email: [info@tintolav.com](mailto:info@tintolav.com) - Sito internet: [www.tintolav.com](http://www.tintolav.com)

Email tecnico competente: [a.conedera@tintolav.com](mailto:a.conedera@tintolav.com)

National contact: Malta: Emergency Ambulance 112  
Accident & Emergency Department 2545 4030

### **1.4. Emergency telephone number**

The UK National Poisons Emergency number +44 (0)870 600 6266  
London: Emergency 24 hour telephone +44 (0) 207188 0100

## **SECTION 2. Hazards identification**

### **2.1. Classification of the substance or mixture**

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms:

None

Hazard Class and Category Code(s):

Nonhazardous

Hazard statement Code(s):

Nonhazardous

### **2.2. Label elements**

Labelling according to Regulation (EC) No 1272/2008:

Pictogram, Signal Word Code(s):

None

Hazard statement Code(s):  
Nonhazardous

Supplemental Hazard statement Code(s):  
EUH208 - Contains 4-tert-Butylcyclohexyl acetate, Hexyl salicylate. May produce an allergic reaction.  
EUH210 - Safety data sheet available on request.

Precautionary statements:  
General  
P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.

Contains (Reg.EC 648/2004):  
5% < 15% cationic surfactants, < 5% perfumes, Dye, D-Limonene ((S)-p-menta-1,8-diene), Benzyl salicylate, a-Hexylcinnamaldehyde, Citronellol, Eugenol, ALPHA ISOMETHYLE IONONE, Geraniol, Geraniol

Content of VOC ready to use condition: 0,81 %

UFI: KXM0-D00Q-T00E-4MSV

### 2.3. Other hazards

The substance / mixture NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

No information on other hazards

## SECTION 3. Composition/information on ingredients

### 3.1 Substances

Irrilevant

### 3.2 Mixtures

Refer to paragraph 16 for full text of hazard statements

Substance	Concentration[ w/w]	Classification	Index	CAS	EINECS	REACH
Fatty acids, C16-18 (even numbered) and C18 unsatd., reaction products with triethanolamine, di-Me sulfate-quaternized	>= 5 < 15%	ATE oral = 5.000,0 mg/kg ATE dermal = 2.000,0 mg/kg	ND	157905-74-3	931-203-0	01-2119463 889-16-000 4
4-tert-Butylcyclohexyl acetate - FEMA 0	>= 0,1 < 1%	Skin Sens. 1B, H317; Aquatic Chronic 2, H411 1 1 ATE oral = 5.000,0 mg/kg ATE dermal = 5.000,0 mg/kg	ND	32210-23-4	250-954-9	01-2119976 286-24
Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides - FEMA 0	>= 0,1 < 1%	Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Corr. 1B, H314; Eye Dam. 1, H318;	ND	68424-85-1	270-325-2	NR

Substance	Concentration[ w/w]	Classification	Index	CAS	EINECS	REACH
		Aquatic Acute 1, H400 100 100 ATE oral = 344,0 mg/kg ATE dermal = 3.340,0 mg/kg ATE inhal = 5,0mg/l/4 h				
Hexyl salicylate - FEMA 0	>= 0,1 < 1%	Skin Irrit. 2, H315; Skin Sens. 1, H317; Eye Irrit. 2, H319; Aquatic Acute 1, H400; Aquatic Chronic 1, H410 1 1 ATE oral = 5.000,0 mg/kg ATE dermal = 5.000,0 mg/kg	ND	6259-76-3	228-408-6	01-2119638 275-36-000 2
ethanol	< 0,1%	Flam. Liq. 2, H225 ATE oral = 7.060,0 mg/kg ATE dermal = 20.000,0 mg/kg ATE inhal = 20.000,0mg/l/4 h	603-002-00-5	64-17-5	200-578-6	01-2119457 610-43
1,2-benzisothiazol-3(2H)-one	< 0,1%	Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; Eye Dam. 1, H318; Aquatic Acute 1, H400 Limits: Skin Sens. 1, H317 %C >=0,05; , EUH208 0,005<= %C <0,05; 1 ATE oral = 1.020,0 mg/kg	613-088-00-6	2634-33-5	220-120-9	NR

## SECTION 4. First aid measures

### 4.1. Description of first aid measures

**Inhalation:**

Air the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated area. If you feel unwell seek medical advice.

**Direct contact with skin (of the pure product):**

Wash thoroughly with soap and running water.

**Direct contact with eyes (of the pure product):**

Wash immediately and thoroughly with running water for at least 10 minutes.

**Ingestion:**

Not hazardous. It's possible to give activated charcoal in water or liquid paraffin medicine

---

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

If medical advice is needed, have product container or label at hand.

**SECTION 5. Firefighting measures**

**5.1. Extinguishing media**

Advised extinguishing agents:

Water spray, CO<sub>2</sub>, foam, dry chemical, depending on the materials involved in the fire.

Extinguishing means to avoid:

Water jets. Use water jets only to cool the surfaces of the containers exposed to fire.

**5.2. Special hazards arising from the substance or mixture**

No data available.

**5.3. Advice for firefighters**

Use protection for the breathing apparatus

Safety helmet and full protective suit.

The spray water can be used to protect the people involved in the extinction

You may also use selfrespirator, especially when working in confined and poorly ventilated area and if you use halogenated extinguishers (Halon 1211 fluobrene, Solkan 123, NAF, etc...)

Keep containers cool with water spray

**SECTION 6. Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

6.1.1 For non-emergency personnel:

Leave the area surrounding the spill or release. Do not smoke

Wear gloves and protective clothing

6.1.2 For emergency responders:

Wear gloves and protective clothing

Eliminate all unguarded flames and possible sources of ignition. No smoking.

Provision of sufficient ventilation.

Evacuate the danger area and, in case, consult an expert.

**6.2. Environmental precautions**

Contain spill with earth or sand.

If the product has entered a watercourse in sewers or has contaminated soil or vegetation, notify it to the authorities.

Discharge the remains in compliance with the regulations

**6.3. Methods and material for containment and cleaning up**

6.3.1 For containment:

Recover the product for reuse, if possible, or for removal. Possibly absorb it with inert material.

Prevent it from entering the sewer system.

6.3.2 For cleaning up:  
After wiping up, wash with water the area and materials involved

6.3.3 Other information:  
None in particular.

#### **6.4. Reference to other sections**

Refer to paragraphs 8 and 13 for more information

## **SECTION 7. Handling and storage**

### **7.1. Precautions for safe handling**

Avoid contact and inhalation of vapors  
At work do not eat or drink.  
See also paragraph 8 below.

### **7.2. Conditions for safe storage, including any incompatibilities**

Keep in original container closed tightly. Do not store in open or unlabeled containers.  
Keep containers upright and safe by avoiding the possibility of falls or collisions.  
Store in a cool place, away from sources of heat and direct exposure of sunlight.

### **7.3. Specific end use(s)**

Industrial Manufacturing:  
Handle with extreme caution.  
Store in a well ventilated place away from heat sources.

Private households (= general public = consumers):  
Handle with care.  
Store in ventilated place away from heat sources,  
Keep the container tightly closed.

Public domain (administration, education, entertainment, services, craftsmen):  
Handle with care. Store in a ventilated area and away from heat, keep the container tightly closed.

## **SECTION 8. Exposure controls/personal protection**

### **8.1. Control parameters**

Related to contained substances:

ethanol:

Component CAS-No. Value Control parameters

Basis

Ethanol-17-64 TWA 5 ppm 1.000

1.920 mg/m<sup>3</sup>

UK. EH40 WEL-Workplace Exposure Limits

Remarks Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used

- Substance: Fatty acids, C16-18 (even numbered) and C18 unsatd., reaction products with triethanolamine, di-Me sulfate-quaternized

DNEL

Systemic effects Long term Workers inhalation = 44 (mg/m<sup>3</sup>)

Systemic effects Long term Workers dermal = 312,5 (mg/kg bw/day)

Systemic effects Long term Consumers inhalation = 13 (mg/m<sup>3</sup>)

Systemic effects Long term Consumers dermal = 187,5 (mg/kg bw/day)

Systemic effects Long term Consumers oral = 7,5 (mg/kg bw/day)

**PNEC**

Sweet water = 0,00191 (mg/l)  
sediment Sweet water = 0,58 (mg/kg/sediment)  
Sea water = 0,000191 (mg/l)  
sediment Sea water = 0,058 (mg/kg/sediment)  
intermittent emissions = 0,0191 (mg/l)  
STP = 2,96 (mg/l)  
ground = 0,115 (mg/kg ground)

- Substance: Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides

**DNEL**

Systemic effects Long term Workers inhalation = 3,96 (mg/m<sup>3</sup>)  
Systemic effects Long term Workers dermal = 5,7 (mg/kg bw/day)  
Systemic effects Long term Consumers inhalation = 1,64 (mg/m<sup>3</sup>)  
Systemic effects Long term Consumers dermal = 3,4 (mg/kg bw/day)  
Systemic effects Long term Consumers oral = 3,4 (mg/kg bw/day)

**PNEC**

Sweet water = 0,0009 (mg/l)  
sediment Sweet water = 12,27 (mg/kg/sediment)  
Sea water = 0,00096 (mg/l)  
sediment Sea water = 13,09 (mg/kg/sediment)  
intermittent emissions = 0,00016 (mg/l)  
STP = 0,4 (mg/l)  
ground = 7 (mg/kg ground)

- Substance: Hexyl salicylate

**DNEL**

Systemic effects Long term Workers inhalation = 0,79 (mg/m<sup>3</sup>)  
Systemic effects Long term Workers dermal = 2083 (mg/kg bw/day)  
Systemic effects Short term Workers inhalation = 0,79 (mg/m<sup>3</sup>)  
Systemic effects Short term Workers dermal = 2083 (mg/kg bw/day)

- Substance: ethanol

**DNEL**

Systemic effects Long term Workers inhalation = 950 (mg/m<sup>3</sup>)  
Systemic effects Long term Workers dermal = 343 (mg/kg bw/day)  
Systemic effects Long term Consumers inhalation = 114 (mg/m<sup>3</sup>)  
Systemic effects Long term Consumers dermal = 206 (mg/kg bw/day)  
Systemic effects Long term Consumers oral = 87 (mg/kg bw/day)

**PNEC**

Sweet water = 0,96 (mg/l)  
sediment Sweet water = 3,6 (mg/kg/sediment)  
Sea water = 0,79 (mg/l)  
sediment Sea water = 2,9 (mg/kg/sediment)  
intermittent emissions = 2,75 (mg/l)  
STP = 580 (mg/l)  
ground = 0,63 (mg/kg ground)

## 8.2. Exposure controls

Appropriate engineering controls:  
Industrial Manufacturing:  
No specific monitoring foreseen

Private households (= general public = consumers):  
No specific checks planned

Public domain (administration, education, entertainment, services, craftsmen):  
No specific monitoring foreseen

Individual protection measures:

(a) Eye / face protection  
Not needed for normal use.

(b) Skin protection

(i) Hand protection  
Handle with gloves. Gloves must be checked before use. Use a technique suitable for removing gloves (without touching the outer surface of the glove) to avoid the skin contact with this product. Dispose of contaminated gloves after use in accordance with current legislation and good laboratory practices. Wash and dry your hands. The selected protective gloves have to satisfy the requirements of EU directive 89/686 / EEC and the resulting EN 374 standards.

Full contact

Material: Nitrile rubber

minimum thickness: 0.11 mm

breakthrough time: 480 min

The choice of an appropriate glove depends not only on the material but also on other quality characteristics which vary from one manufacturer to another.

For the choice of the type of gloves to use consult the supplier / manufacturer of the gloves.

Observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.

(ii) Other  
Wear normal work clothing.

(c) Respiratory protection  
Not needed for normal use.

(d) Thermal hazards  
No hazard to report

Environmental exposure controls:

Use according to good working practices to avoid pollution into the environment.

## SECTION 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical and chemical properties	Value	Determination method
Appearance	Liquid	
Colour	Blue	
Odour	characteristic	
Odour threshold	not determined	
pH	3-4	
Melting point/freezing point	not determined	

Physical and chemical properties	Value	Determination method
Initial boiling point and boiling range	not determined	
Flash point	> 65°C	
Evaporation rate	irrelevant	
Flammability (solid, gas)	irrelevant	
Upper/lower flammability or explosive limits	not determined	
Vapour pressure	not determined	
Vapour density	not determined	
Relative density	1,00 - 0,9 g/cm <sup>3</sup> @ 20 °C	
Solubility	Completely soluble in water	
Water solubility	Completely soluble in water	
Partition coefficient: n-octanol/water	not determined	
Auto-ignition temperature	not determined	
Decomposition temperature	not determined	
Viscosity	undefined	
Explosive properties	not explosive	
Oxidising properties	non-oxidizing	

### 9.2. Other information

Content of VOC ready to use condition: 0,81 %

## SECTION 10. Stability and reactivity

### 10.1. Reactivity

No reactivity hazards

### 10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.

### 10.3. Possibility of hazardous reactions

There are no hazardous reactions

### 10.4. Conditions to avoid

Nothing to report

### 10.5. Incompatible materials

It can generate inflammable gases to contact with elementary metals, nitrides, inorganic sulfide, strong reducing agents.

It can generate toxic gases to contact with inorganic sulfide, strong reducing agents.

### 10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

## SECTION 11. Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

ATE(mix) oral = 224.836,6 mg/kg

ATE(mix) dermal = ∞

ATE(mix) inhal = ∞

(a) acute toxicity: 4-tert-Butylcyclohexyl acetate: Rats (10 per dose, sex and strain not reported) were administered 4-tert-butylcyclohexyl acetate by gavage at 5000 mg/kg-bw. No information on mortality was reported  
Rabbits (4, sex and strain not reported) were administered 4-tert-butylcyclohexyl acetate dermally at 5000 mg/kg-bw. One rabbit died.

ethanol: LD50 Oral-rat-7.060 mg/kg

Remarks: Lungs, Thorax, or Respiration: Other changes.

LC50 Inhalation-rat-10:0-20000 ppm

(b) skin corrosion/irritation: 4-tert-Butylcyclohexyl acetate: Rabbits (species, sex and number not specified) were administered 4-tert-butylcyclohexyl acetate dermally to the ears and backs. Observations of the backs included slight erythema after 1 and 5 min, severe erythema and slight edema at 15 min, and severe erythema and edema at 20 hours. On day 8, slight redness and severe scaling were observed. Observations of the ears included severe erythema and edema with blistering after 20 hours. Severe necrosis was recorded on day 8. (Bhatia, S.P., et al., Food and Chemical Toxicology 46 (2008) S36-S41) 4-tert-Butylcyclohexyl acetate was irritating to rabbit skin

Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides: rabbit Result: Method: DOT Corrosive  
Exposure time: 12:0 am

ethanol: Skin-rabbit

Result: Irritating to skin. -12:0 am

(c) serious eye damage/irritation: ethanol: Eyes-rabbit

Result: Mild eye irritation-12:0 am

(Draize Test)

4-tert-Butylcyclohexyl acetate: Albino rabbits (3/sex dose not specified) were instilled 0.1 mL aliquot of 0.625% solution (vehicle not reported) into the right eye of each rabbit with no further treatment while the left eye served as control. Scores were recorded according to the Draize scale. Slight to moderate irritation with conjunctival chemosis and discharge were observed in all three rabbits (mean score for redness and 1.9 for 1 chemosis). All eyes cleared by day 4. (Bhatia, S.P., et al., Food and Chemical Toxicology 46 (2008) S36-S41) 4-tert-Butylcyclohexyl acetate was irritating to rabbit eyes.

Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides: rabbit Result: Caustic Method: DOT

(d) respiratory or skin sensitisation: Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides: Buehler guinea pig Test Classification: Did not cause sensitization on laboratory animals.

Result: not sensitizing Method: OECD Test Guideline 406

(e) germ cell mutagenicity: 4-tert-Butylcyclohexyl acetate: Salmonella typhimurium strains TA98, TA100, TA1535, TA1537 and Ta 1538 were exposed to 4-tert-butylcyclohexyl acetate at 8 to 5000 g/plate in a bacterial reverse mutation assay in the presence and absence of metabolic activation. Positive and negative controls were used but their response was not provided. Cytotoxicity was observed at and above 200 g/plate.

4-tert-Butylcyclohexyl acetate was not mutagenic in this assay.

(f) carcinogenicity: based on available data, the classification criteria are not met.

(g) reproductive toxicity: ethanol: Reproductive toxicity-Human-female-Oral

Effects on Newborn: Apgar score (human only). Effects on Newborn: Other measures or neonatal effects.

Effects on Newborn: Drug dependence.

(h) specific target organ toxicity (STOT) single exposure: based on available data, the classification criteria are not met.

(i) specific target organ toxicity (STOT) repeated exposure 4-tert-Butylcyclohexyl acetate: In a modified developmental toxicity screening test (OCED TG 421), Crl: CD pregnant (SD) rats were administered 4-tert-butylcyclohexyl acetate (a mixture of 71% 28% trans and cis) in corn oil by gavage at 0, 40, 160 or 640 mg/kg-bw per day during gestation days 7-20. Rats were Caesarean-sectioned on day 21 of gestation and examined for number and distribution of corpora lutea, implantation sites and placenta. Live and dead fetuses and early and late resorptions were recorded. Fetuses were examined for sex ratio, gross external alterations and skeletal and soft tissue alterations. There were no effects on

maternal body weights, weight gain, food consumption or organ weights. Pup viability, body weights, external observations and microscopic examination showed no significant alterations that could be related to the administration of the test substance.

NOAEL (maternal or developmental toxicity) = 640 mg/kg-bw/day (based on no effects at the highest dose tested)

(j) aspiration hazard: based on available data, the classification criteria are not met.

**Health hazards:**

Contact with eyes: Accidental contact of the product with the eyes can cause irritation.

Skin contact: The product is not an irritant. Repeated and prolonged direct contact can degrease and irritate the skin causing dermatitis in some cases.

Ingestion: The ingested product can cause irritation of the mucous membranes of the throat and digestive system with consequent abnormal digestive symptoms and intestinal disorders.

Inhalation: Prolonged exposure to vapors or mists of the product can cause irritation to the respiratory tract.

**Related to contained substances:**

Fatty acids, C16-18 (even numbered) and C18 unsatd., reaction products with triethanolamine, di-Me sulfate-quaternized:

Oral, LD50: 5000 mg / kg (rat)

Dermal, LD50:> 2000 mg / kg (rat)

LD50 (rat) Oral (mg/kg body weight) = 5000

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 2000

**4-tert-Butylcyclohexyl acetate:**

LD50 (rat) Oral (mg/kg body weight) = 5000

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 5000

**Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides:**

LD50 (rat) Oral (mg/kg body weight) = 344

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 3340

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 5

**Hexyl salicylate:**

LD50 (rat) Oral (mg/kg body weight) = 5000

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 5000

**ethanol:**

ROUTES of EXPOSURE: the substance can be absorbed into the body by inhalation of its fumes and ingestion.

INHALATION RISK: A harmful contamination of the air will be reached quite slowly due to evaporation of the substance at 20 C.

Effects of short-term exposure: the substance is irritating to the eyes. Inhalation of high vapour can concetrazioni cause irritation of the eyes and respiratory tract. The substance may cause effects on the central nervous system effects of REPEATED EXPOSURE or long term: the liquid degreasing the skin features. The substance may have an effect on the high central nervous system respiratory tract, causing irritation, headaches, fatigue and lack of concentration. See Notes.

ACUTE HAZARDS/Symptoms INHALATION Cough. Headaches. Fatigue. Drowsiness.

CUTE CUTE.

EYE Redness. Pain. Burning.

SWALLOWED burning sensation. Headaches. Confusion. Vertigo. State of unconsciousness.

N O T and consumption of ethanol during pregnancy can have adverse effects on the unborn child. Chronic ethanol ingestion can cause cirrhosis of the liver.

LD50 (rat) Oral (mg/kg body weight) = 7060

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 20000

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 20000

**1,2-benzisothiazol-3(2H)-one:**

LD50 (rat) Oral (mg/kg body weight) = 1020

### 11.2. Information on other hazards

No data available.

## SECTION 12. Ecological information

### 12.1. Toxicity

Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides:

Related to contained substances:

Fatty acids, C16-18 (even numbered) and C18 unsatd., reaction products with triethanolamine, di-Me sulfate-quaternized:

fish, CL50 : 1,91 mg/l (OECD 203 (96h))

daphnia, CE50 : 2,23 mg/l (EU Method C.2 (48h))

alga, C150 : 2,14 mg/l (OECD 201 (72h))

C(E)L50 (mg/l) = 1,91

4-tert-Butylcyclohexyl acetate:

Golden ide (*Leuciscus idus*) were exposed to 4-tert-butylcyclohexyl acetate at nominal concentrations of 0, 10, 13, 16 and 20 mg/L under static conditions for 48 hours. EF Marlowet was used as a solubilizer. Mortality was 0, 10, 100 and 80% at 10, 13, 16 and 20 mg/L.

48-h LC50 = 14 mg/L

Water fleas (*Daphnia magna*) were exposed to 4-tert-butylcyclohexyl acetate at nominal concentrations of 2.8 to 28.4 mg/L (measured concentrations, 2.4 to 28.4 mg/L) under static conditions for 48 hours.

48-h EC50 = 23.4 mg/L

C(E)L50 (mg/l) = 14

Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides:

C(E)L50 (mg/l) = 0,01 100

100

ethanol:

C(E)L50 (mg/l) = 11200

1,2-benzisothiazol-3(2H)-one:

C(E)L50 (mg/l) = 0,8

Use according to good working practices to avoid pollution into the environment.

### 12.2. Persistence and degradability

Related to contained substances:

Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides:

Biodegradability:

OECD Confirmatory > 90% Test Method: OECD 303 A Modified SCAS Test Exposure time: 99% 7 d > Method: OECD Test 302 Evolution CO2 Concentration: 5 mg/litre Exposure time: 28 d Result: Readily biodegradable.

95.5% Method: OECD 301 B

### 12.3. Bioaccumulative potential

No data available.

---

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No PBT/vPvB ingredient is present

**12.6. Endocrine disrupting properties**

No data available.

**12.7. Other adverse effects**

No adverse effects

**SECTION 13. Disposal considerations**

**13.1. Waste treatment methods**

Do not reuse empty containers. Dispose of them in accordance with the regulations in force. Any remaining product should be disposed of according to applicable regulations by addressing to authorized companies.  
Recover if possible. Operate according to local or national regulations

**SECTION 14. Transport information**

**14.1. UN number or ID number**

Not included in the scope of application regulations concerning the transport of dangerous goods: by road (ADR); by rail (RID); by air (ICAO / IATA); by sea (IMDG).

**14.2. UN proper shipping name**

None

**14.3. Transport hazard class(es)**

None

**14.4. Packing group**

None

**14.5. Environmental hazards**

None

**14.6. Special precautions for user**

No data available.

---

**14.7. Maritime transport in bulk according to IMO instruments**

It is not intended to carry bulk

**SECTION 15. Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

REGULATION (EU) No 1357/2014 - waste:  
HP14 - Ecotoxic

**15.2. Chemical safety assessment**

The supplier has made an assessment of chemical safety

**SECTION 16. Other information**

**16.1. Other information**

Description of the hazard statements exposed to point 3

- H317 = May cause an allergic skin reaction.
- H411 = Toxic to aquatic life with long lasting effects.
- H302 = Harmful if swallowed.
- H312 = Harmful in contact with skin.
- H314 = Causes severe skin burns and eye damage.
- H318 = Causes serious eye damage.
- H400 = Very toxic to aquatic life.
- H315 = Causes skin irritation.
- H319 = Causes serious eye irritation.
- H410 = Very toxic to aquatic life with long lasting effects.
- H225 = Highly flammable liquid and vapour.

Classification based on data of all mixture components

Main normative references:

- Directive 1999/45/EC
- Directive 2001/60/EC
- Regulation 1272/2008/EC
- Regulation 2010/453/EC

\*\* The information contained herein is based on our knowledge at the date above.

Related solely to the product and do not constitute a guarantee of a particular quality.

It is the duty of the user to ensure that these are appropriate and complete information regarding the specific use intended.

This data sheet cancels and replaces any previous edition.