

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product code : Hygienfresh Odorblok

Trades code : A32-000

Product line: Hygienfresh

UFI: 1X51-K0PA-F00E-375N

1.2. Relevant identified uses of the substance or mixture and uses advised against

Spray Remove multi-action odors, even for more persistent odors

Sectors of use:

Industrial Manufacturing[SU3], Private households (= general public = consumers)[SU21], Public domain (administration, education, entertainment, services, craftsmen)[SU22]

Product category:

Perfumes, Fragrances

Uses advised against

Do not use for purposes other than those listed

1.3. Details of the supplier of the safety data sheet

Tintolav s.r.l. - Via M. D' Antona 7 - 10028 Trofarello (TO) Tel. 011/649.68.27 Fax 011/649.67.42

Email: info@tintolav.com - Sito internet: www.tintolav.com

Email tecnico competente: a.conedera@tintolav.com

National contact: Malta: Emergency Ambulance 112

Accident & Emergency Department 2545 4030

1.4. Emergency telephone number

The UK National Poisons Emergency number +44 (0)870 600 6266

London: Emergency 24 hour telephone +44 (0) 207188 0100

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms:

GHS05, GHS09

Hazard Class and Category Code(s):

Eye Dam. 1, Aquatic Acute 1

Hazard statement Code(s):

H318 - Causes serious eye damage.

H400 - Very toxic to aquatic life. (1)

If brought into contact with eyes, the product causes serious damages to eyes, such as an opaque cornea or injury to iris.

The product is dangerous for the environment as it is very toxic to aquatic organisms

2.1.2 Additional information:

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008:

Pictogram, Signal Word Code(s):
GHS05, GHS09 - Danger



Hazard statement Code(s):
H318 - Causes serious eye damage.
H400 - Very toxic to aquatic life. (1)

Supplemental Hazard statement Code(s):
EUH208 - Contains Benzyl salicylate, α -Hexylcinnamaldehyde. May produce an allergic reaction.

Precautionary statements:**General**

- P101 - If medical advice is needed, have product container or label at hand.
- P102 - Keep out of reach of children.

Prevention

- P273 - Avoid release to the environment.
- P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Response

- P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 - Immediately call a POISON CENTER/doctor/physician

Disposal

- P501 - Dispose of contents / container in accordance with local and national regulations.

Contains:

aqua, isopropyl alcohol, parfum, alketh-3, ricinus communis oil, ethoxydiglycol, alcohol, benzalkonium chloride, C12-14 pareth-3, zinc ricinoleate, tetrasodium edta, Benzyl salicylate, Hexyl cinnamal, Tetramethyl acetyloctahydronaphthalenes, Geraniol, Citronellol, Eugenol, Coumarin, Hydroxy citronellal, Alpha isomethyl ionone amines, C12-16-alkyldimethyl, dimethicone, steareth-21.

Content of VOC ready to use condition: 6,32 %

UFI: 1X51-K0PA-F00E-375N

2.3. Other hazards

Based on the available data, no PBT or vPvB substances are present in accordance with Regulation (EC) 1907/2006, annex XIII

Based on available data, there are no substances that interfere with the Endocrine System in accordance with Regulation (EU) 2017/2100

No information on other hazards

SECTION 3. Composition/information on ingredients

3.1 Substances

Irrilevant

3.2 Mixtures

Substance	Concentration[w/w]	Classification	Index	CAS	EINECS	REACH
Propan-2-ol - FEMA 2929	$\geq 1 < 5\%$	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336 ATE oral = 2.100,000 mg/kg ATE dermal = 2.100,000 mg/kg ATE inhal = 29,000 mg/l/4 h	603-117-00-0	67-63-0	200-661-7	ND
Alcohols, C12-15-branched and linear, ethoxylated (>2.5 moles EO)	$\geq 1 < 5\%$	Acute Tox. 4, H302; Eye Dam. 1, H318; Aquatic Chronic 3, H412 1 1 ATE oral > 300,000 mg/kg ATE dermal > 2.000,000 mg/kg	ND	106232-83-1	932-186-2	ND
ethanol	$\geq 0,1 < 1\%$	Flam. Liq. 2, H225 ATE oral = 7.060,000 mg/kg ATE dermal = 20.000,000 mg/kg ATE inhal = 20.000,000 mg/l/4 h	603-002-00-5	64-17-5	200-578-6	01-2119457 610-43
Alcohols, C12-14, ethoxylated	$\geq 0,1 < 1\%$	Eye Dam. 1, H318; Aquatic Acute 1, H400 ATE oral = 2.000,000 mg/kg ATE dermal = 2.000,000 mg/kg ATE inhal = 1,600 mg/l/4 h	ND	68439-50-9	ND	ND
Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides - FEMA 0	$\geq 0,1 < 1\%$	Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 100 100 ATE oral = 344,000 mg/kg ATE dermal = 3.340,000 mg/kg ATE inhal = 5,000 mg/l/4 h	ND	68424-85-1	270-325-2	ND
Benzyl salicylate	$\geq 0,1 < 1,00\%$	Skin Sens. 1B, H317; Eye Irrit. 2, H319; Aquatic Chronic 3,	607-754-00-5	118-58-1	204-262-9	01-2119969 442-31

Substance	Concentration[w/w]	Classification	Index	CAS	EINECS	REACH
		H412 1 1 ATE oral = 2.227,000 mg/kg				
α -Hexylcinnamaldehyde	< 0,1%	Skin Sens. 1, H317; Aquatic Acute 1, H400; Aquatic Chronic 2, H411 ATE oral = 2.450,000 mg/kg	ND	101-86-0	202-983-3	01-2119533 092-50

Fractionated global values

H302 = 3,29	H318 = 3,68	H412 = 2,98	H315 = 0,45
H312 = 0,36	H314 = 0,36	H400 = 0,99	H225 = 5,02
H411 = 0,23	H319 = 5,25	H336 = 4,31	H341 = 0,00
H331 = 0,00	H311 = 0,00	H301 = 0,02	H373 = 0,02
H317 = 0,50	H410 = 0,14	H335 = 0,02	H226 = 0,00
H304 = 0,00	H361 = 0,00		

SECTION 4. First aid measures

4.1. Description of first aid measures

Inhalation:

Air the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated area. If you feel unwell seek medical advice.

Direct contact with skin (of the pure product):

Wash thoroughly with soap and running water.

Direct contact with eyes (of the pure product):

Wash immediately and thoroughly with running water, keeping eyelids open for at least 10 minutes, then protect your eyes with a dry sterile gauze. Seek medical advice immediately

Do not use eye drops or ointments of any kind before the examination or advice from an oculist.

Ingestion:

Not hazardous. It's possible to give activated charcoal in water or liquid paraffin medicine

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

If medical advice is needed, have product container or label at hand.

Immediately call a POISON CENTER/doctor/physician

SECTION 5. Firefighting measures

5.1. Extinguishing media

Advised extinguishing agents:

Water spray, CO₂, foam, dry chemical, depending on the materials involved in the fire.

Extinguishing means to avoid:

Water jets. Use water jets only to cool the surfaces of the containers exposed to fire.

5.2. Special hazards arising from the substance or mixture

No data available.

5.3. Advice for firefighters

Use protection for the breathing apparatus

Safety helmet and full protective suit.

The spray water can be used to protect the people involved in the extinction

You may also use selfrespirator, especially when working in confined and poorly ventilated area and if you use halogenated extinguishers (Halon 1211 fluobrene, Solkan 123, NAF, etc...)

Keep containers cool with water spray

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel:

Leave the area surrounding the spill or release. Do not smoke

Wear mask, gloves and protective clothing.

6.1.2 For emergency responders:

Wear protective gloves and clothing.

Eliminate all open flames and possible sources of ignition.

Not smoking.

Provide adequate ventilation.

Evacuate the danger area and, if necessary, consult an expert.

6.2. Environmental precautions

Contain spill with earth or sand.

If the product has entered a watercourse in sewers or has contaminated soil or vegetation, notify it to the authorities.

Discharge the remains in compliance with the regulations

6.3. Methods and material for containment and cleaning up

6.3.1 For containment:

Rapidly recover the product, wear a mask and protective clothing

Recover the product for reuse, if possible, or for removal. Possibly absorb it with inert material.

Prevent it from entering the sewer system.

6.3.2 For cleaning up:

After wiping up, wash with water the area and materials involved

6.3.3 Other information:

None in particular.

6.4. Reference to other sections

Refer to paragraphs 8 and 13 for more information

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Avoid contact and inhalation of vapors
Wear protective gloves/protective clothing/eye protection/face protection.
At work do not eat or drink.
See also paragraph 8 below.

7.2. Conditions for safe storage, including any incompatibilities

Keep in original container closed tightly. Do not store in open or unlabeled containers.
Keep containers upright and safe by avoiding the possibility of falls or collisions.
Store in a cool place, away from sources of heat and direct exposure of sunlight.

7.3. Specific end use(s)

Industrial Manufacturing:
Handle with extreme caution.
Store in a well ventilated place away from heat sources.

Private households (= general public = consumers):
Handle with care.
Store in ventilated place away from heat sources,
Keep the container tightly closed.

Public domain (administration, education, entertainment, services, craftsmen):
Handle with care. Store in a ventilated area and away from heat, keep the container tightly closed.

SECTION 8. Exposure controls/personal protection**8.1. Control parameters**

Related to contained substances:

Propan-2-ol:
TLV: TWA 200 ppm 400 ppm as STEL A4 (not classifiable as a human carcinogen); (ACGIH 2004).
MAK: 200 ppm 500 mg/m peak limitation Category: II (2); Risk group for pregnancy: C; (DFG 2004).

ethanol:

Component CAS-No. Value Control parameters

Basis

Ethanol-17-64 TWA 5 ppm 1.000

1.920 mg/m³

UK. EH40 WEL-Workplace Exposure Limits

Remarks Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used

- Substance: Propan-2-ol

DNEL

Systemic effects Long term Workers inhalation = 500 (mg/m³)

Systemic effects Long term Workers dermal = 888 (mg/kg bw/day)

Systemic effects Long term Consumers inhalation = 89 (mg/m³)

Systemic effects Long term Consumers dermal = 26 (mg/kg bw/day)

Systemic effects Long term Consumers oral = 26 (mg/kg bw/day)

PNEC

Sweet water = 140,9 (mg/l)

sediment Sweet water = 552 (mg/kg/sediment)

Sea water = 140,9 (mg/l)

sediment Sea water = 552 (mg/kg/sediment)

STP = 2251 (mg/l)

ground = 28 (mg/kg ground)

- Substance: ethanol

DNEL

Systemic effects Long term Workers inhalation = 950 (mg/m³)

Systemic effects Long term Workers dermal = 343 (mg/kg bw/day)

Systemic effects Long term Consumers inhalation = 114 (mg/m³)

Systemic effects Long term Consumers dermal = 206 (mg/kg bw/day)

Systemic effects Long term Consumers oral = 87 (mg/kg bw/day)

PNEC

Sweet water = 0,96 (mg/l)

sediment Sweet water = 3,6 (mg/kg/sediment)

Sea water = 0,79 (mg/l)

sediment Sea water = 2,9 (mg/kg/sediment)

STP = 580 (mg/l)

ground = 0,63 (mg/kg ground)

- Substance: Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides

DNEL

Systemic effects Long term Workers inhalation = 3,96 (mg/m³)

Systemic effects Long term Workers dermal = 5,7 (mg/kg bw/day)

Systemic effects Long term Consumers inhalation = 1,64 (mg/m³)

Systemic effects Long term Consumers dermal = 3,4 (mg/kg bw/day)

Systemic effects Long term Consumers oral = 3,4 (mg/kg bw/day)

PNEC

Sweet water = 0,0009 (mg/l)

sediment Sweet water = 12,27 (mg/kg/sediment)

Sea water = 0,00096 (mg/l)

sediment Sea water = 13,09 (mg/kg/sediment)

STP = 0,4 (mg/l)

ground = 7 (mg/kg ground)

- Substance: α -Hexylcinnamaldehyde

DNEL

Systemic effects Long term Workers inhalation = 0,000078 (mg/m³)

Systemic effects Short term Workers inhalation = 0,00628 (mg/m³)

PNEC

Sweet water = 0,03 (mg/l)

sediment Sweet water = 47,7 (mg/kg/sediment)

Sea water = 0,003 (mg/l)

sediment Sea water = 4,77 (mg/kg/sediment)

ground = 9,51 (mg/kg ground)

8.2. Exposure controls

Appropriate engineering controls:

Industrial Manufacturing:

No specific monitoring foreseen

Private households (= general public = consumers):

No specific checks planned

Public domain (administration, education, entertainment, services, craftsmen):



No specific monitoring foreseen

Individual protection measures:

(a) Eye / face protection

When handling the pure product use safety glasses (spectacles cage) (EN 166).

(b) Skin protection

(i) Hand protection

Handle with gloves. Gloves must be checked before use. Use a technique suitable for removing gloves (without touching the outer surface of the glove) to avoid the skin contact with this product. Dispose of contaminated gloves after use in accordance with current legislation and good laboratory practices. Wash and dry your hands. The selected protective gloves have to satisfy the requirements of EU directive 89/686 / EEC and the resulting EN 374 standards.

Full contact

Material: Nitrile rubber

minimum thickness: 0.11 mm

breakthrough time: 480 min

The choice of an appropriate glove depends not only on the material but also on other quality characteristics which vary from one manufacturer to another.

For the choice of the type of gloves to use consult the supplier / manufacturer of the gloves.

Observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.

(ii) Other

When handling the pure product wear full protective skin clothing.

(c) Respiratory protection

Not needed for normal use.

(d) Thermal hazards

No hazard to report

Environmental exposure controls:

Use according to good working practices to avoid pollution into the environment.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical and chemical properties	Value	Determination method
Physical state	Liquid	
Colour	straw yellow	
Odour	Characteristic	
Odour threshold	not determined	
Melting point/freezing point	not determined	
Boiling point or initial boiling point and boiling range	not determined	
Flammability	nonflammable	
Lower and upper explosion limit	not determined	
Flash point	> 65 °C	ASTM D92
Auto-ignition temperature	not determined	

Physical and chemical properties	Value	Determination method
Decomposition temperature	not determined	
pH	not determined	
Kinematic viscosity	not determined	
Solubility	Completely soluble in water	
Water solubility	Completely soluble in water	
Partition coefficient n-octanol/water (log value)	not determined	
Vapour pressure	not determined	
Density and/or relative density	0.990-1,02 g/cm ³	
Relative vapour density	not determined	
Particle characteristics	irrelevant	

9.2. Other information

Content of VOC ready to use condition: 6,32 %

9.2.1 Information with regard to physical hazard classes

Irrilevant

9.2.2 Other safety characteristics

Irrilevant

SECTION 10. Stability and reactivity**10.1. Reactivity**

No reactivity hazards

10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.

10.3. Possibility of hazardous reactions

There are no hazardous reactions

10.4. Conditions to avoid

Nothing to report

10.5. Incompatible materials

It can generate inflammable gases to contact with elementary metals, nitrides, inorganic sulfide, strong reducing agents.

It can generate toxic gases to contact with inorganic sulfide, strong reducing agents.

10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11. Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

ATE(mix) oral = 9.739,2 mg/kg

ATE(mix) dermal = ∞

ATE(mix) inhal = ∞

(a) acute toxicity: ethanol: LD50 Oral-rat-7.060 mg/kg

Remarks: Lungs, Thorax, or Respiration: Other changes.

LC50 Inhalation-rat-10:0-20000 ppm

Benzyl salicylate: Oral Rat LD50 = 2227 mg/kg bw

α -Hexylcinnamaldehyde: Oral (rat) LD50: 2450 mg/kg

(b) skin corrosion/irritation: Propan-2-ol: Skin-rabbit

Result: Mild skin irritation

ethanol: Skin-rabbit

Result: Irritating to skin. -12:0 am

Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides: rabbit Result: Method: DOT Corrosive

Exposure time: 12:0 am

Benzyl salicylate: Skin - rabbit

Result: No skin irritation

(OECD Test Guideline 404)

(c) serious eye damage/irritation: If brought into contact with eyes, the product causes serious damages to eyes, such as an opaque cornea or injury to iris.

ethanol: Eyes-rabbit

Result: Mild eye irritation-12:0 am

(Draize Test)

Propan-2-ol: Eyes-rabbit

Result: Eye irritation- 24 h

Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides: rabbit Result: Caustic Method: DOT

Benzyl salicylate: Eyes - In vitro study

Result: Moderate eye irritation

(OECD Test Guideline 437)

Eyes - rabbit

Result: Irritating to eyes.

(Draize Test)

(d) respiratory or skin sensitisation: Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides: Buehler guinea pig Test Classification: Did not cause sensitization on laboratory animals.

Result: not sensitizing Method: OECD Test Guideline 406

(e) germ cell mutagenicity: based on available data, the classification criteria are not met.

(f) carcinogenicity: based on available data, the classification criteria are not met.

(g) reproductive toxicity: ethanol: Reproductive toxicity-Human-female-Oral

Effects on Newborn: Apgar score (human only). Effects on Newborn: Other measures or neonatal effects.

Effects on Newborn: Drug dependence.

(h) specific target organ toxicity (STOT) single exposure: based on available data, the classification criteria are not met.

(i) specific target organ toxicity (STOT) repeated exposure based on available data, the classification criteria are not met.

(j) aspiration hazard: Benzyl salicylate: in vivo assay - mouse

May cause allergic skin reaction.

(OECD Test Guideline 429)

Related to contained substances:

Propan-2-ol:

ROUTES of EXPOSURE: the substance can be absorbed into the body by inhalation of its fumes.

INHALATION RISK: A harmful contamination of the air will be reached quite slowly due to evaporation of the substance at 20 C; However, for spraying or scattering, much more quickly.

Effects of short-term exposure: the substance is irritating to the eyes and the respiratory tract the substance may cause effects on the central nervous system, causing depression. Much greater exposure to the OEL may lead to unconsciousness.

Effects of REPEATED EXPOSURE or long term: the liquid degreasing the skin features.

ACUTE HAZARDS/Symptoms INHALATION Cough. Vertigo. Drowsiness. Headaches. Sore throat. See If Swallowed. CUTE CUTE.

EYE Redness.

INGESTION abdominal pain. Difficulty in breathing. Nausea. State of unconsciousness. Vomiting. (Further see inhalation).

N O T and use of alcoholic beverages enhances the harmful effect.

LD50 (rat) Oral (mg/kg body weight) = 2100

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 2100

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 29

Alcohols, C12-15-branched and linear, ethoxylated (>2.5 moles EO):

LD50 (rat) Oral (mg/kg body weight) > 300

LD50 Dermal (rat or rabbit) (mg/kg body weight) > 2000

ethanol:

ROUTES of EXPOSURE: the substance can be absorbed into the body by inhalation of its fumes and ingestion.

INHALATION RISK: A harmful contamination of the air will be reached quite slowly due to evaporation of the substance at 20 C.

Effects of short-term exposure: the substance is irritating to the eyes. Inhalation of high vapour can cause irritation of the eyes and respiratory tract. The substance may cause effects on the central nervous system effects of

REPEATED EXPOSURE or long term: the liquid degreasing the skin features. The substance may have an effect on the high central nervous system respiratory tract, causing irritation, headaches, fatigue and lack of concentration. See Notes.

ACUTE HAZARDS/Symptoms INHALATION Cough. Headaches. Fatigue. Drowsiness. CUTE CUTE.

EYE Redness. Pain. Burning.

SWALLOWED burning sensation. Headaches. Confusion. Vertigo. State of unconsciousness.

N O T and consumption of ethanol during pregnancy can have adverse effects on the unborn child. Chronic ethanol ingestion can cause cirrhosis of the liver.

LD50 (rat) Oral (mg/kg body weight) = 7060

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 20000

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 20000

Alcohols, C12-14, ethoxylated:

Oral > LD50 2000 mg/kg (rat)

LD50 (rat) Oral (mg/kg body weight) = 2000

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 2000

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 1,6

Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides:

LD50 (rat) Oral (mg/kg body weight) = 344

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 3340

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 5

Benzyl salicylate:

LD50 (rat) Oral (mg/kg body weight) = 2227

α -Hexylcinnamaldehyde:

LD50 (rat) Oral (mg/kg body weight) = 2450**11.2. Information on other hazards**

No data available.

11.2.1. Endocrine disrupting properties

Based on available data, there are no substances that interfere with the Endocrine System in accordance with Regulation (EU) 2017/2100

SECTION 12. Ecological information**12.1. Toxicity**

Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides:

Related to contained substances:

Propan-2-ol:

Toxicity to fish LC50-Pimephales promelas (fathead minnow)-9, 640.00 mg/l-96 h

Toxicity to daphnia and other aquatic invertebrates

-EC50 Daphnia magna (Water flea)-5, 102.00 mg/l- 24 h

EC50 Immobilization-Daphnia magna (Water flea)-6.851 mg/l- 24h

C(E)L50 (mg/l) = 5102 1

1

Alcohols, C12-15-branched and linear, ethoxylated (>2.5 moles EO):

C(E)L50 (mg/l) = 1

ethanol:

C(E)L50 (mg/l) = 11200

Alcohols, C12-14, ethoxylated:

EC50 < 1 mg/l (Literaturwert)

NOEC/21 d 0.77 mg/l (Daphnia magna)

C(E)L50 (mg/l) = 0,19

Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides:

C(E)L50 (mg/l) = 0,01 100

100

Benzyl salicylate:

Zebra fish (Brachydanio rerio) 96 hour LC50 = 1.03 mg/L

48 hour LC50 = 1.4mg/l

C(E)L50 (mg/l) = 1,03 1

1

 α -Hexylcinnamaldehyde:

Freshwater Fish Toxicity: acute LC50 >1-10 mg/L

Freshwater Invertebrates Toxicity: acute EC <1 mg/L

Algal Toxicity: acute EC <1 mg/L.

C(E)L50 (mg/l) = 0,99

The product is dangerous for the environment as it is very toxic to aquatic organisms following acute exposure.

Use according to good working practices to avoid pollution into the environment.

12.2. Persistence and degradability

Related to contained substances:

Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides:

Biodegradability:

OECD Confirmatory > 90% Test Method: OECD 303 A Modified SCAS Test Exposure time: 99% 7 d > Method: OECD Test 302 Evolution CO2 Concentration: 5 mg/litre Exposure time: 28 d Result: Readily biodegradable.

95.5% Method: OECD 301 B

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

Based on the available data, no PBT or vPvB substances are present in accordance with Regulation (EC) 1907/2006, annex XIII

12.6. Endocrine disrupting properties

Based on available data, there are no substances that interfere with the Endocrine System in accordance with Regulation (EU) 2017/2100

12.7. Other adverse effects

No adverse effects

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Do not reuse empty containers. Dispose of them in accordance with the regulations in force. Any remaining product should be disposed of according to applicable regulations by addressing to authorized companies.

Recover if possible. Send to authorized discharge plants or for incineration under controlled conditions. Operate according to local and National rules in force

SECTION 14. Transport information

14.1. UN number or ID number

ADR/RID/IMDG/ICAO-IATA: 0000

ADR exemption because compliance with the following characteristics:

Combination packagings: per inner packaging 5 L per package 30 kg

Inner packagings placed in shrink-wrapped or stretch-wrapped trays: per inner packaging 5 L per package 20 kg

14.2. UN proper shipping name

ADR/RID/IMDG: MATERIA PERICOLOSA PER L'AMBIENTE, LIQUIDA, N.A.S. (Propan-2-olo, etanolo, Alcoli, C12-14, etossilati, Composti di ammonio quaternario, benzil-C12-16-alkyldimetil, cloruri, Salicilato di benzile, α -Hexylcinnamaldehyde, Sale sodico dell'acido etilendiamintetraacetico, 1-(1,2,3,4,6,7,8,8a-Octahydro-2,3,8,8-tetramethyl-2-naphthyl)ethan-1-one, p-cresolo, o-Cresol)
ADR/RID/IMDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Propan-2-ol, ethanol, Alcohols, C12-14, ethoxylated, Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides, Benzyl salicylate, α -Hexylcinnamaldehyde, tetrasodium ethylenediaminetetraacetate, 1-(1,2,3,4,6,7,8,8a-Octahydro-2,3,8,8-tetramethyl-2-naphthyl)ethan-1-one, p-cresol, o-cresol)
ICAO-IATA: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Propan-2-ol, ethanol, Alcohols, C12-14, ethoxylated, Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides, Benzyl salicylate, α -Hexylcinnamaldehyde, tetrasodium ethylenediaminetetraacetate, 1-(1,2,3,4,6,7,8,8a-Octahydro-2,3,8,8-tetramethyl-2-naphthyl)ethan-1-one, p-cresol, o-cresol)

14.3. Transport hazard class(es)

ADR/RID/IMDG/ICAO-IATA: Class : 9
ADR/RID/IMDG/ICAO-IATA: Label :
ADR: Tunnel restriction code : --
ADR/RID/IMDG/ICAO-IATA: Limited quantities : 5 L
IMDG - EmS : F-A, S-F

14.4. Packing group

ADR/RID/IMDG/ICAO-IATA: III

14.5. Environmental hazards

ADR/RID/ICAO-IATA: Product is environmentally hazardous
IMDG: Marine polluting agent : Yes

14.6. Special precautions for user

No data available.

14.7. Maritime transport in bulk according to IMO instruments

It is not intended to carry bulk

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso category:
E1 - ENVIRONMENTAL HAZARDS

REGULATION (EU) No 1357/2014 - waste:
HP14 - Ecotoxic

Substances in the Candidate List (REACH Article 59)
Based on available data, no SVHC substances are present

15.2. Chemical safety assessment

The supplier has made an assessment of chemical safety

SECTION 16. Other information**16.1. Other information**

Points modified compared to previous release: 2.1. Classification of the substance or mixture, 2.2. Label elements, 2.3. Other hazards, 3.2 Mixtures, 4.1. Description of first aid measures, 4.3. Indication of any immediate medical attention and special treatment needed, 8.1. Control parameters, 9.2.1 Information with regard to physical hazard classes, 9.2.2 Other safety characteristics, 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008, 11.2. Information on other hazards, 12.1. Toxicity, 12.2. Persistence and degradability, 12.6. Endocrine disrupting properties, 14.1. UN number or ID number, 14.2. UN proper shipping name

Description of the hazard statements exposed to point 3

H225 = Highly flammable liquid and vapour.

H319 = Causes serious eye irritation.

H336 = May cause drowsiness or dizziness.

H302 = Harmful if swallowed.

H318 = Causes serious eye damage.

H412 = Harmful to aquatic life with long lasting effects.

H400 = Very toxic to aquatic life.

H312 = Harmful in contact with skin.

H314 = Causes severe skin burns and eye damage.

H317 = May cause an allergic skin reaction.

H411 = Toxic to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008

H318 - Causes serious eye damage. Classification procedure: Calculation method

H400 - Very toxic to aquatic life. Classification procedure: Calculation method

Main normative references:

Directive 1999/45/EC

Directive 2001/60/EC

Regulation 1272/2008/EC

Regulation 2010/453/EC

** The information contained herein is based on our knowledge at the date above.

Related solely to the product and do not constitute a guarantee of a particular quality.

It is the duty of the user to ensure that these are appropriate and complete information regarding the specific use intended.

This data sheet cancels and replaces any previous edition.